Angelus Legacy Series Can Seamer: Model 10P







Standard Features

The Model 10P Angelus seamer incorporates a free-standing stainless steel machine enclosure, with door interlocks. Built for easy maintenance and operation, this machine is rated for speeds up to 80 CPM.

- Variable speed motor drive
- PLC and touch screen control
- Reciprocating cover separator knife
- One set of can and end change parts

- No can/no cover feed
- Head spin machine
- Grease lubrication
- Tool kit and instruction manual



Angelus Legacy Series Can Seamer: Model 10P

Optional Features

- Steam vacuum
- Under cover gassing
- Modification for oil filters available
- Rotary embossing type cover marker
- Titanium Nitride-coated Angelloy® seaming rolls with ceramic bearings
- Titanium Nitride-coated Angelloy seaming chucks

- Toppers or packers
- Filler drive with safety clutch
- Filler/seamer connections
- Can manufacturing

Technical Specifications	English	Metric
Number of seaming heads	1	1
Output speed range	30-80 CPM	30-80 CPM
Min/Max Can Diameter	202-404	54.0 mm-108.0 mm
Min/Max Can Diameter (Optional)	108-404	38.1mm-108.0mm
Min/Max Can Height	108-708	38.1mm-190.5mm
Min/Max Can Height (Optional)	108-1000	38.1mm-254.0mm
Min./Max Can Height (SV)	111-700	42.9mm-177.8mm
Transfer Chain Pitch Can Centers	Random	Random
Horsepower/Electrical	3-5 Hp	2-4 Kw
Electrical Controls	24 Volt DC	24 Volt DC
Steam Supply	330°F @ 60 psi	165°C @ 4 bars
Net Weight (Approx.)	2,000 lbs.	907 Kg
Gross Weight Domestic (Approx.)	2,700 lbs.	1225 Kg
Gross Weight Export (Approx.)	3,000 lbs.	1360 Kg

Angelus | Carr Centritech | Consolidated | Continental/Closetech | Hema Mateer Burt | Multi-Tech Systems | OnTrack | Zepf Change Parts

