

Angelus Legacy Series Can Seamer: Model 40P



Standard Features

The Model 40P Angelus seamer incorporates a free-standing stainless steel machine enclosure, with door interlocks. Built for easy maintenance and operation, this machine is rated for speeds up to 275 CPM.

- Variable speed motor drive
- Reciprocating cover separator knife
- Revolving 4-head rotary seaming turret
- Wide range of accessories and attachments
- One set of can and end change parts

- No can/no cover feed
- Grease lubrication
- Electric brake
- Disk feed infeed
- Tool kit and instruction manual

BW Packaging Systems represents the collective capabilities of Barry-Wehmiller packaging companies including, Accraply, BW Flexible Systems, BW Integrated Systems, Pneumatic Scale Angelus and Synerlink. Through their diverse capabilities, these companies can collectively provide everything from a single piece of equipment to fully integrated packaging systems for a wide range of industries, including: food and beverage, personal care, container manufacturing, pharmaceutical and medical devices, household products, paper products and textiles, industrial and automotive, and converting, printing and publishing. For more information, go to *BWPackagingSystems.com*



Optional Features

- Steam vacuum
- Under cover gassing
- Single roll cover separator
- Rotary embossing type cover marker
- Titanium Nitride-coated Angelloy® seaming rolls with ceramic bearings
- Titanium Nitride-coated Angelloy seaming chucks

- Toppers or packers
- Cover feed chute with vibrator
- Filler connecting parts
- Random worm infeed
- Magnetic downstacker chute with vibrator
- Mechanical driven machine height
- Can manufacturing

Technical Specifications	English	Metric
Number of seaming stations	4	4
Output speed range	20-275 CPM	20-275 CPM
Min/Max Can Diameter	202-404	54.0 mm-108.0 mm
Min/Max Can Diameter (Optional)	108-404	38.1 mm-108.0 mm
Min/Max Can Height	108-700	38.1 mm-177.8 mm
MSLF (Optional)	108-812	38.1-222.3 mm
MSLF (SV & UCG)	111-700	42.9-177.8 mm
DF (Optional)	108-1000	38.1-254.0 mm
DF (SV & UCG)	111-700	42.9-177.8 mm
Transfer Chain Pitch Can Centers (MSLF)	6.00"	152.4 mm
Transfer Chain Pitch Centers (DF)	Random	Random
Horsepower/Electrical	5 hp	4 Kw
Electrical Controls	24 Volt DC	24 Volt DC
CO ² /Nitrogen Gas	100 psi @ 70F	6.9 bar @ 21C
Steam Supply	330 psi @ 85F	5.9 bar @ 165C
Net Weight (Approx.)	5,900 lbs.	2,676 kg
Gross Weight Domestic MSLF (Approx.)	6,900 lbs.	3,130 kg
Gross Weight Export MSLF (Approx.)	7,300 lbs.	3,311 kg

Angelus | Carr Centritech | Consolidated | Continental/Closetech | Hema Mateer Burt | Multi-Tech Systems | OnTrack | Zepf Change Parts

Pneumatic Scale Angelus 4485 Allen Road Stow, OH 44224 USA

t. +1 (330) 923-0491 psangelus.com

