

## Angelus Legacy Series Can Seamer: Model 56P







## **Standard Features**

The Model 56P Angelus seamer incorporates a free-standing stainless steel machine enclosure, with door interlocks, and a seaming turret safety clutch. This machine is rated for speeds up to 300 CPM.

- Variable speed motor drive
- Revolving 3-head rotary seaming turret, with seaming levers
- Head spin machine
- One set of can and end change parts

- Proven box style knockout and cap centering cams
- Soft rise lower chuck cam
- No can/no cover feed
- Grease lubrication
- Electric brake

BW Packaging Systems represents the collective capabilities of Barry-Wehmiller packaging companies including, Accraply, BW Flexible Systems, BW Integrated Systems, Pneumatic Scale Angelus and Synerlink. Through their diverse capabilities, these companies can collectively provide everything from a single piece of equipment to fully integrated packaging systems for a wide range of industries, including: food and beverage, personal care, container manufacturing, pharmaceutical and medical devices, household products, paper products and textiles, industrial and automotive, and converting, printing and publishing. For more information, go to *BWPackagingSystems.com* 



## **Optional Features**

- Steam vacuum
- Under cover gassing
- Single roll cover separator
- Rotary cover marking attachment
- Titanium Nitride-coated Angelloy® seaming rolls with ceramic bearings
- Titanium Nitride-coated Angelloy seaming chucks

- Toppers or packers
- Cover feed chute with vibrator
- Filler connecting parts
- Random worm infeed
- Magnetic downstacker chute with vibrator
- Mechanical driven machine height
- Can manufacturing

Technical Specifications	English	Metric
Number of seaming stations	3	3
Output speed range	10-300 CPM	10-300 CPM
Min/Max Can Diameter	501-610	128.6-167.4 mm
Min/Max Can Diameter (Optional)	307-701	87.3-179.4 mm
Min/Max Can Height	308-910	88.9-244.5 mm
Min/Max Can Height DF (Optional)	108-1204	38.1-311.2 mm
Min/Max Can Height MSLF (Optional)	108-1109	38.1-293.7 mm
Min/Max Can Height MSLF (SV & UCG)	308-910	88.9-244.5 mm
Min/Max Can Height MSLF (SV & UCG)	208-1000	63.5-254.0 mm
Transfer Chain Pitch Can Centers (MSLF)	10.50"	266.7 mm
Transfer Chain Pitch Centers (DF)	Random	Random
Horsepower/Electrical	3-7.5 hp	2-6 Kw
Electrical Controls	24 Volt DC	24 Volt DC

## Angelus | Carr Centritech | Consolidated | Continental/Closetech | Hema Mateer Burt | Multi-Tech Systems | OnTrack | Zepf Change Parts

Pneumatic Scale Angelus 4485 Allen Road Stow, OH 44224 USA

t. +1 (330) 923-0491 psangelus.com

