



Angelus Legacy Series Can Seamer: Model 60L



Standard Features

The Model 60L Angelus seamer incorporates a base-mounted stainless steel machine enclosure, with door interlocks. This machine is rated for speeds up to 500 CPM.

- Six seaming stations
- One set of can and end change parts
- Single roll cover separator
- Gear-driven lower lifters with seven point lubrication system
- Second operation off-seam setting
- Automatic stop control system
- Grease lubrication
- PLC and touch screen control
- Pneumatic no can/no cover feed
- Variable speed motor drive
- Tool kit and instruction manual

Angelus Legacy Series Can Seamer: Model 6oL

Optional Features

- Steam vacuum
- Under cover gassing
- Titanium Nitride-coated Angelloy® seaming rolls with ceramic bearings
- Titanium Nitride-coated Angelloy seaming chucks
- Toppers or packers
- Filler connecting parts
- Random worm infeed
- Semi-automatic grease lubrication
- Magnetic downstacker chute with vibrator
- Nickel-plated machine
- Can manufacturing

Technical Specifications	English	Metric
Number of seaming stations	6	6
Output speed range	175-500 CPM	175-500 CPM
Min/Max Can Diameter	200-404	50.8-108.0 mm
Min/Max Can Diameter (Optional)	112	44.5 mm
Min/Max Can Height (UCG & Atmos)	108-712	38.1-196.9 mm
Min/Max Can Height (UCG & SV)	111-712	42.8-196.9 mm
Min. Can Height (CM & Atmos - Optional)	108	38.1 mm
Min. Can Height (UCG & SV - Optional)	107	36.5 mm
Min. Can Height (Optional)	1300	330.2 mm
Transfer Chain Pitch Can Centers	6.00"	152.4 mm
Filler Drive	1 Rev/Can	Direction Reversible
Horsepower/Electrical	7.5-10 hp	6-8 kW
Electrical Controls	24 VDC	24 VDC
CO ² /Nitrogen Gas Supply Pressure	100 psi @ 70F	6.9 bar @ 21C
Net Weight (Approx.)	6150 lbs.	2,790 kg
Gross Weight (Approx.)	7250 lbs.	3,289 kg

**Angelus | Carr Centritech | Consolidated | Continental/Closetech | Hema
Mateer Burt | Multi-Tech Systems | OnTrack | Zepf Change Parts**

Pneumatic Scale Angelus

4485 Allen Road
Stow, OH 44224 USA

t. +1 (330) 923-0491
psangelus.com