



A BARRY-WEHMILLER COMPANY

## Series 2003, 2006 & 2008 HDS Closetech High-Speed Double Seamers



### Key Features

- Power driven can holding chuck assemblies
- Innovative design reduces gearing by as much as 18%
- Fewer seaming stations reduce the quantity of tooling and setup time
- One set of change parts included with the base machine
- Individual 1st and 2nd operation seaming roll shanks allow overlap seaming and full range of can sizes without the need for lever replacement
- Three screw cover feed design provides optimum separation and control of all end types
- Equipped with solid state covertrip and low coverstack controls

## Series 2003, 2006 & 2008 HDS

# Closetech High-Speed Double Seamers

The 2000 HDS series has been designed with the versatility necessary to accommodate the full range of can sizes manufactured in your plant, with the speed capability to match today's needs. Height changeovers may be accomplished in a matter of minutes. This quick change feature is the result of a totally new concept which provides for the support and driving of all height change related components directly from the Top Housing. This unique design eliminates the need for sliding shaft and key fits found in other Double Seamers available today.

Diameter changes can be accomplished in a matter of several hours. With optional quick change features, diameter changes of one hour may be achieved.

The 2000 HDS Series of High Speed Double Seamers has been value engineered to meet the current and future needs of the can manufacturing industry. Their design incorporates many new features, and proven concepts developed over our 90+ years of seaming machine building experience.



Technical Specifications 2000 HDS	2003 3- SPINDLE	2006 6- SPINDLE	2008 8- SPINDLE
Maximum Speed (dependent on can size, type, and type of drive)	450 CPM	900 CPM	1200 CPM
Diameter range of cans handled	211 - 603*	202 - 404*	200 - 300*
Height range of cans handled with standard tin line	208 - 910	110 - 800**	110 - 800**
Net weight, approximate lbs/kg	5850/2647 kg	5900/2670 kg	5950/2698 kg
Height max.	90.72"/230.43 cm	89.12"/226.36 cm	89.12"/226.36 cm
Width	54.0"/137.0 cm	54.0"/137.0 cm	54.0"/137.0 cm
Length, basic	74.2"/188.5 cm	74.2"/188.5 cm	74.2"/188.5 cm

\* With appropriate change parts, outside this range, consult sales office

\*\* Height to .012 may be handled with raised tin line

USA | AUSTRALIA | BELGIUM | CANADA | HONG KONG | UNITED KINGDOM



A BARRY-WEHMILLER COMPANY

4485 ALLEN RD | STOW, OH 44224 USA | +1 (330) 923-0491

WWW.PNEUMATICSCALEANGELUS.COM | SALES@PSANGELUS.COM